


Datasheet

SLAM Hornet 1LED 12V

ATEXOR code	SH1LEDA12
Manufacturing date	Q4/2020
Product description	Explosion protected portable luminary
ATEX & IECEx marking	 Ex II 2 G Ex eb mb op is IIC T4 Gb Ex II 2 D Ex tb op is IIIC T90°C Db
Temperature classification	T4 (internal) T70 °C (external)
Operating temperature	-20°C ... +40°C
Light source	1 LED module with SafeEye® technology
Light emitted at source	2350 lm
Luminous flux (measured)	1340 lm
Colour temperature	5000 K +/- 10 %
Colour rendering index	>80
Photobiological safety	Exempt group (No marking required, safe in normal use)
Supply Voltage (min-max)	9-15VAC/DC
Supply Current (typical)	12V~1,5 A
Electrical class	Class 3 (<50V)
Input power (P)	17 W
Power factor	>0,8
Cable	Standard cable H07RN-F
Plug	2P+E, 3P, 2P
Enclosure	Dissipative materials (PC & TPE)
Ingress protection	IP66 (A-version)
Weight (without cable and plug)	1,72 kg
Accessories	SLAM Click'n Fix magnetic fixing system Protective film
Warranty	



Datasheet
SLAM Hornet 1LED 12V

Product model	Dimensions / mm	
	L	Ø
SLAM® Hornet 1LED A (cable, No Socket)	580	115

