LED TASKLIGHT

SATL100



CLEAR, EVEN LIGHT PRECISELY WHERE **YOU NEED IT**

With a bank of 30 high-power LEDs, the SA LUMIN EX LED Tasklight gives you clear, even light output so you can see and work efficiently. It's ideal for quick inspections, emergency response work, rope access work and tasks in remote or inaccessible areas. As it's rechargeable there are no trailing cables to trip over, and a fast recharge time of 1-3 hours gives up to 6 hours use. The versatile, ergonomic design means you can hang it, stand it up, lie it down or hold it exactly where you need it.



BENEFITS

- ATEX and IECEx Certified for Zones 0, 1 and 2 (gas), 20, 21 and 22 (dust)
- High Power LED Light Output
- Rechargeable no trailing cables
- Up to 6 hours use per charge
- Waterproof and dustproof (IP66)
- Low charge warning
- Lightweight & highly ergonomic
- Tough and durable
- Retractable hook
- Fast charge time 3 hours
- Available with 5-way charging rack

CORE PRODUCT INFORMATION

SA LUMIN EX LED Rechargeable Tasklight offering 6 hours continuous use c/w charger, mains supply lead, & car socket lead Order Code: SATL100

SA LUMIN EX LED Rechargeable Tasklight Set c/w 5 Tasklights, 5-Way Charging Rack & Mains Supply Lead Order Code: SATL100/CR5

SA LUMIN Tasklight Holster enabling hands-free operation of the Tasklight c/w adjustable strap Order Code: SATL/HR







SA LUMIN Tasklight Magnetic Bracket c/w anti-static strap and stainless steel spring-loaded buckle Order Code: SATL/MB

SA LUMIN Tasklight Stabilising Base Unit Order Code: SATL/BU

SA LUMIN Tasklight Adjustable Floor Stand Order Code: SATL/FS4



SPECIFICATIONS

CERTIFICATION

(II 1G Ex ia op is IIC T4 Ga ⟨ II 1D Ex ia IIIC T100°C Da (Ex) I M1 Ex ia I Ma

CHARGING TIME

Full charge - 3 hours 80% charge - 1 hour

OPERATING TEMPERATURE

-20°C to +60°C

INGRESS PROTECTION

BATTERY

Lithium-lon

LIGHT OUTPUT 600 lux at 1m with 30 high power LEDs

WEIGHT 615q (Tasklight only) 425g (Single Charger only) 7.7kg (Charging Rack only)

DIMENSIONS

289mm x 76mm x 46.5mm (Tasklight only) 140mm x 134.5mm x 104mm (Single Charger) 850mm x 270mm x 180mm (Charging Rack)

ELECTRONICS

Low charge warning

CHARGER SUPPLY VOLTAGE

200-250VAC (Single Charger & Charging Rack) 12-14VDC (Single Charger only)

CHARGING TEMPERATURE

0°C to +40°C



































