EXTENSION REEL

PNER

THE WORLD'S FIRST **'OFF THE SHELF' EXTENSION REEL**

Designed and built to withstand the most demanding conditions, the SA POWERNET EX Extension Reel is highly portable, stable, waterproof and dustproof. It is available in a wide range of variants accommodating different plug and socket combinations, cable types and voltages.





BENEFITS

- ATEX Certified for Zones 1 and 2 (gas), 21 and 22 (dust)
- INMETRO Certified
- Highly portable
- Tough stainless steel construction
- Waterproof and dustproof
- Large number of variants available

SPECIFICATIONS

Ex db eb IIC T5 Gb Ex tb IIIC T100°C Db IP66

OPERATING TEMPERATURE

VOLTAGE

24VAC, 42VAC, 110VAC, 230VAC

INPUT

1 x 16A Plug

OUTPUT

16.2kg (with HOFR cable)

25m (or as required)

CORE PRODUCT INFORMATION

SA POWERNET EX Extension Reel 110V c/w 1 x 16A CEAG plug, 1 x 16A CEAG socket, and 25m of braided HOFR cable Order Code: PNER110EX/25HRE/CEA

SA POWERNET EX Extension Reel 230V c/w 1 x 16A CEAG plug, 1 x 16A CEAG socket, and 25m of braided HOFR cable Order Code: PNER230EX/25HRE/CEA



ATX & STAHL connectors, different cable lengths and types are also available in 24V and 42V versions - please contact SA Equip for more details.





⟨Ex⟩ II 2 G D

INGRESS PROTECTION

-20°C to +40°C

1 x 16A Socket

DIMENSIONS

490mm (h) x 390mm (w) x 400mm (d)

WEIGHT

CABLE LENGTH



ZONE 2











