

ISIS-ml - GSM EMERGENCY CALL POINT

TELEPHONE / INTERCOM SYSTEM EQUIPMENT



ISIS-ml model 1 button with optional Led indicator



• Weather Proof
IP66

PRODUCT DESCRIPTION

The ISIS-ml type Emergency call point is based on a SMC enclosure with cold rolled steel faceplate, offers increased resistance to vandalism, and ensure that the primary function of communications is maintained at all times.

The ISIS-ml Emergency call point have been widely used at highways, railway platforms, university, college campuses, streets, public square, car-parks, police stations, outside buildings, shopping malls, industrial areas etc.

MAIN FEATURES

- ✓ Robust housing, constructed of thick steel to anti-vandal
- ✓ Hands free operation
- ✓ Programmable for speed-dialing (PPT)
- ✓ Can be programmed remotely (via SMS)
- ✓ Single or Dual button autodial options with remote programming
- ✓ Non-volatile memory
- ✓ Weather protection IP65-IP66
- ✓ Fast-fit terminal connection
- ✓ Optional power supply by solar panel

MECHANICAL DATA

• Housing	Body:Composite Sheet Molding Compound (SMC) Faceplate: cold rolled steel
• Call method	By pick up handset
• Diameter	240H X 140L X 106Wmm (with handset)
• Weight	Approx. 2.5 kg
• Color	Orange color, Red or blue color as demand

ELECTRICAL DATA

• Direct current supply	12 Vdc/2A
• Consumption	0.3 to 1.5 W
• Communication Type	Full duplex
• Ringer volume	75~80dB(A) @ 1 m
• Program Method	Remote programming by SMS
• Frequency	Dual-Band UMTS/HSDPA 900/2100MHz Quad-Band GSM/GPRS/EDGE 850/900/1800/1900MHz
• Conversation Mode:	Hands free

ENVIRONMENT

• Operating temperature	-25°C to +65°C
• Storage temperature	-30°C to +70°C
• Relative humidity (non -condensing)	Max. 95 %
• Degree of protection	IP 66 as per EN60529
• Impact Rating (IK)	IK 10

ORDER NUMBER	DESCRIPTION
T139E011	GSM phone with 1 call button, standard orange color
T139E012	GSM phone with 2 call button, standard orange color

Optional color * : *=R(Red) / *=B(Blue)