

TM 132 - GSM CLEAN-ROOM PHONE

TELEPHONE / INTERCOM SYSTEM EQUIPMENT



• Weather Proof
IP66

PRODUCT DESCRIPTION

Designed for clean room, the TM132 hands free phone body housing with metal enclosure, the front panel is covered with polyester fiber in which there are no any holes , this prevents the accumulation of microorganisms and allows for hygienic processing.

TM132 can meet the needs of critical environments such as hospitals, pharmaceutical labs and diagnostic centers, medical institutions, pharmaceutical production, chemical and food industries.

MAIN FEATURES

- ✓ Robust housing, constructed of thick steel to anti-vandal
- ✓ Hands free operation
- ✓ Programmable for speed-dialing (PPT)
- ✓ Can be programmed remotely (via SMS)
- ✓ Single or Dual button autodial options with remote programming
- ✓ Non-volatile memory
- ✓ Weather protection IP66
- ✓ Fast-fit terminal connection
- ✓ Optional power supply by solar panel

MECHANICAL DATA

• Material	Body : Alluminum Front panel: Polyester fiber
• Call method	By keypad or Push button
• Diameter	225H x 130L x 36W(mm)
• Weight	Approx. 2.0 kg
• Color	White color for font panel

ELECTRICAL DATA

• Direct current supply	12 Vdc/2A
• Consumption	0.3 to 1.5 W
• Communication Type	Full duplex
• Ringer volume	75 dB(A) @ 1 m
• Program Method	Remote programming by SMS
• Frequency	Dual-Band UMTS/HSDPA 900/2100MHz Quad-Band GSM/GPRS/EDGE 850/900/1800/1900MHz
• Conversation Mode:	Hands free

ENVIRONMENT

• Operating temperature	-30°C to +65°C
• Storage temperature	-40°C to +75°C
• Relative humidity (non -condensing)	Max. 95 %
• Degree of protection	IP 66 as per EN60529
• Impact Rating (IK)	IK 10

ORDER NUMBER	DESCRIPTION
TM132s-b1	GSM phone wall mounting with 1 call button
TM132s-cl	GSM phone wall mounting with keypad